## **TRAILER - SINGLE TEMPERATURE**



## A-500 Whisper Pro

## Enter the city at night

- · Compliant with even the most stringent inner city noise regulations
- Electronically governed NRMM compliant 4-speed engine
- Fuel consumption monitoring
- Most accurate temperature control in the market
- Fastest pulldown
- $\cdot$  Fully variable airflow independent of unit engine speed
- Quietest high-capacity unit in the Market

PERFORMANCE				
REFRIGERATION CAPACITY HIGH SPEED		REFRIGERATION CAPACITY PIEK MODE		
Capacity on engine power 0°C	18,200 W	Capacity on engine power 0°C	15,900	
Capacity on engine power -20°C	10,000 W	Capacity on electrical stand by 0°C	13,800	
Capacity on electrical stand by 0°C	12,350 W	Capacity on electrical stand by -20°C	6,850	
Capacity on electrical stand by -20°C	8,400 W			
AIRFLOW: INDEPENDENT FROM UNIT ENGINE SPEI	ED			
Airflow volume @ 0 Pa static pressure - Default @ Pull Down	5,000 m3/hr			
Airflow volume @ 0 Pa static pressure - Max @ Pull Down	5,000 m3/hr			
Airflow volume @ 0 Pa static pressure - Default @ Set Point	3,400 m3/hr			
Airflow volume @ 0 Pa static pressure - Max @ Set Point	5,000 m3/hr			

TECHNICAL DATA				
ENGINE		ELECTRICAL STAND BY MOTOR		
Maintenance Interval	3000 hrs	Voltage / Phase / Frequency	400/3/50 460/3/60	
Number of cylinders	4	Rating	9.3 kW	
Capacity	2,1 L			